



4G HD1080 Dome Camera



Sensor	1/2.5" CMOS sensor,24M progressive scan
Lens	2.8mm / 3.6mm / 6mm / 8mm / 12mm (selectable)
Video quality	1920 x 1080 at 25fps
Minimum illumination	Color: 0.1lux/F1.2(AGC-ON) / B&W: 0.02lux/F1.2(AGC-ON)
Lighting	Built-in LED Lighting (for over 40meter)
Video S/N ratio	50dB (AGC off)
Video Stream	H.264 over TCP/UDP/HTTP/FTP/RTP/RTSP
Protocols	TCP/IP, HTTP, FTP, DHCP, DNS, DDNS, RTP, RTCP, NTP, SMTP, IGMP
Local Storage	Micro SD Card (max. 128GB)
Day/Night selection	Auto / Color / Black&White
White balance	Auto / Outdoor / Indoor
Backlight compensation	Enable / Disable
Shutter Time	1/5 ~ 1/4000
Mobile Network	FDD-LTE, TDD-LTE, WCDMA/HSPA+, TD-SCDMA, GSM/GPRS/EDGE
Frequency Band	LTE: B1/B3/B8/B38/B39/B40/B41 WCDMA: 2100/900MHz TD-SCDMA: B34/B39 GSM/GPRS/EDGE: 900/1800MHz
Image compression	H.264 / JPEG
Operating temperature	-10°C to 50°C (Fanless)
Operating humidity	90% or less, Non-condensing
MTBF	80,000 hours
Power supply	DC12V2A
Weight	800g
Dimension	H:60mm W:60mm L: 200mm

*Photo is for reference only.

HIS Technologies Limited

Unit 2005, 20/F, Fook Yip Building, 53-57 Kwai Fung Crescent,
Kwai Chung, N.T., Hong Kong.
Tel: (852) 31658507 Fax: (852) 37471892