



## Ultra-HD IP Camera



### Specifications

Sensor	1/2.5-inch Sony IMX274 Starvis CMOS
Lens	2.8mm / 4mm (selectable)
Video quality	3840 x 2160 at 25fps
Minimum illumination	Color: 0.1lux/F1.2(AGC-ON) / B&W: 0.02lux/F1.2(AGC-ON)
LED Lighting	Built-in Low-energy LED Infra-red Lighting
Video S/N ratio	50dB (AGC off)
Video Stream	H.264 / H.265 over TCP/UDP/HTTP/FTP/RTP/RTSP
Day/Night selection	Auto/Color/Black&White
White balance	Auto/Outdoor/Indoor
Shutter Time	1/5 ~ 1/4000
AGC	Auto
Gamma	Auto
Network	RJ-45 port in 10/100Mbps
Image compression	H.264 / JPEG
Operating temperature	-10°C to 50°C (Fanless)
Operating humidity	90% or less, Non-condensing
MTBF	80,000 hours
Power supply	12V DC / POE
Power consumption	7 Watt
Weight (gun-type)	600g
Dimension (gun-type)	L:200mm W:60mm H:60mm
Weight (gun-type)	700g
Dimension (gun-type)	H:150.0mm D:200.0mm

\*Photo is for reference only.

Room 2804, 28/F, Fook Yip Building, 53-57 Kwai Fung Crescent, New Territories, Hong Kong  
Telephone: (852) 3165-8507 Fax: (852) 3747-1892